



We help you shine.™



REVOLUTION 2000™
PREMIUM FLOOR COATING

116 REVOLUTION 2000™

shine on.

PREMIUM FLOOR COATING

A technologically advanced, high solids, acrylic polymer coating designed to achieve a durable, brilliant wet-look shine.

Product Packaging*



PROD CODE: 116FS
 SIZE: 2.50 US gallons (9.5 liters)
 ORDER QTY: 2 per case



PROD CODE: 116FSE
 SIZE: 2.64 US gallons (10 liters)
 ORDER QTY: 2 per case

*Multi-Language Label.



PROD CODE: 116MPE
 SIZE: 1.06 US gallons (4 liters)
 ORDER QTY: 4 per case

*Multi-Language Label.

* Special packaging for specific requirements available upon request.

With **fewer coats** needed
 you **reduce cost** and **labor**.

Recommended Floor Surfaces:

Vinyl composition tile ("VCT") and most types of terrazzo, marble concrete and quarry tile.

Ideal for floors where maintenance occurs 4-7 days per week.

Directions for use: INITIAL APPLICATION

1. Remove old coating and sealer.
 2. Neutralize floor using a neutral cleaner or EnviroStar Green™ All Purpose Neutralizer.
 3. Rinse floor again with clean, cold water and allow to dry.
 4. Apply 3 coats of REVOLUTION 2000 Floor Coating with a clean, synthetic mop.
 5. Allow floor to dry thoroughly between coats and prior to burnishing.
- NOTE: To prevent contamination do not pour unused product from bucket into original container.

Directions for use: ROUTINE MAINTENANCE

1. Sweep floor daily with a dust mop.
2. To clean floor use mop or scrubber with neutral cleaner.
3. Restore shine as needed with floor maintainer, no more than twice per week.
4. Burnish as desired with UHS floor machine and pad.
5. As needed, perform a deep scrub and re-coat applying an additional 1-2 coats of REVOLUTION 2000 Floor Coating.
6. Allow floor to dry thoroughly between coats and prior to burnishing.
7. Strip floor when desired results cannot be achieved with routine maintenance.

Product Data:

Description	Polymer emulsion	Coverage	2000 to 2500 ft ² /gal 49 to 61 m ² /liter	Buffability	Excellent
Appearance	Milky white	Fragrance	Slight ammoniacal	Removability ASTM D1792-06	Excellent
Non-volatile solids ASTM D2834-95 (2008)	28%	Slip Resistance UL TM410	Meets requirements	Detergent Resistance ASTM D3207-92 (2008)	Excellent
Specular Gloss (60°) ASTM D1455-87 (2008)	>85	Shelf Life ASTM D1791-93 (2008)	1 year	Drying Time	About 30 minutes
Viscosity (Brookfield) @ 68°F (20°C)	<10 centipoise	Density ASTM D1475-98 (2008)	8.7 lb/gal @ 68°F 1.04 kg/L @ 20°C	Freeze/Thaw ASTM D3209-93 (2008)	Passes 3 cycles

MSDS sheets available for download at www.pioneer-eclipse.com

VOC
 (40 CFR Part 59 Subpart C) 0.04%



Floor Coating and Finishing materials
 as to slip resistance only. 42E6

Pioneer Eclipse®

©2011 Amano Pioneer Eclipse Corporation® • 1 Eclipse Road • PO Box 909 • Sparta, NC 28675 USA
 1-800-367-3550 • 1-336-372-8080 • Fax: 1-336-372-2895 • www.pioneer-eclipse.com