



We help you shine.™

**EnviroStar Green™**  
LOW MAINTENANCE FLOOR COATING

# 123 EnviroStar Green™

shine on.

## LOW MAINTENANCE FLOOR COATING

An excellent, low maintenance green coating with outstanding resistance to scuffs, scratches, black heel marks and detergent scrubbing.

### Product Packaging\*



**PROD CODE: 123FS**  
SIZE: 2.50 US gallons (9.5 liters)  
ORDER QTY: 2 per case



**PROD CODE: 123MPE**  
SIZE: 1.06 US gallons (4 liters)  
ORDER QTY: 4 per case

\*Multi-Language Label.

\* Special packaging for specific requirements available upon request.

## Our **No Buff** formula with a long lasting **gloss**.

### Recommended Floor Surfaces:

Vinyl composition tile ("VCT"), Linoleum and Marmoleum flooring.

### Directions for use: INITIAL APPLICATION

1. Remove old coating and sealer.
2. Neutralize floor using a neutral cleaner or EnviroStar Green All Purpose Neutralizer.
3. Rinse floor again with clean, cold water and allow to dry.  
OPTIONAL: Apply 2 thin coats of EnviroStar Green Floor Sealer to protect high traffic areas and old or porous floors.
4. Apply 4-6 coats of EnviroStar Green Low Maintenance Floor Coating with a clean, synthetic mop.  
NOTE: Do not exceed an initial application of a combined 6 coats of coating and sealer.
5. Allow floor to dry thoroughly between coats.  
NOTE: To prevent contamination, do not pour unused product from bucket into original container.

### Directions for use: ROUTINE MAINTENANCE

1. Sweep floor daily with a dust mop.
2. To clean floor use mop or scrubber with neutral cleaner.
3. As needed, perform a deep scrub and re-coat applying an additional 1-2 coats of EnviroStar Green Low Maintenance Floor Coating.
4. Allow floor to dry thoroughly between coats.
5. Strip floor with recommended EnviroStar Green Floor Stripper when desired results cannot be achieved with routine maintenance.

### Product Data:



CARB compliant



Recognized for Safer Chemistry  
www.epa.gov/dfe

<b>Description</b>	Polymer emulsion	<b>Coverage</b>	2500 to 3000 ft <sup>2</sup> /gal 61 to 74 m <sup>2</sup> /liter	<b>Removability</b> ASTM D1792-06	Excellent
<b>Appearance</b>	Milky white	<b>Fragrance</b>	Faintly acetic (non-ammoniated)	<b>Detergent Resistance</b> ASTM D3207-92 (2008)	Excellent
<b>Non-volatile solids</b> ASTM D2834-95 (2008)	20%	<b>Slip Resistance</b> UL TM410	Meets requirements	<b>Drying Time</b>	30 minutes
<b>Specular Gloss (60°)</b> ASTM D1455-87 (2008)	>85	<b>Shelf Life</b> ASTM D1791-93 (2008)	1 year	<b>Freeze/Thaw</b> ASTM D3209-93 (2008)	Passes 3 cycles
<b>Viscosity (Brookfield)</b> @ 68°F (20°C)	<10 centipoise	<b>Density</b> ASTM D1475-98 (2008)	8.6 lb/gal @ 68°F 1.03 kg/L @ 20°C	<b>VOC</b> (40 CFR Part 59 Subpart C)	0.78%

MSDS sheets available for download at [www.pioneer-eclipse.com](http://www.pioneer-eclipse.com)



Floor Coating and Finishing materials  
as to slip resistance only. 42E6

# Pioneer Eclipse®

©2011 Amano Pioneer Eclipse Corporation® • 1 Eclipse Road • PO Box 909 • Sparta, NC 28675 USA  
1-800-367-3550 • 1-336-372-8080 • Fax: 1-336-372-2895 • [www.pioneer-eclipse.com](http://www.pioneer-eclipse.com)