



We help you shine.™

**EnviroStar Green™**  
SATIN FLOOR COATING

# 125 EnviroStar Green™

shine on.

## SATIN FLOOR COATING

An advanced green floor coating designed to provide a highly durable satin coating for use in hospitals and nursing homes.

### Product Packaging\*



**PROD CODE: 125FS**  
SIZE: 2.50 US gallons (9.5 liters)  
ORDER QTY: 2 per case



**PROD CODE: 125MPE**  
SIZE: 1.06 US gallons (4 liters)  
ORDER QTY: 4 per case

\*Multi-Language Label.

\* Special packaging for specific requirements available upon request.

## Our *green* solution for a *satin* floor coating.

### Recommended Floor Surfaces:

Vinyl composition tile ("VCT"), Linoleum and Marmoleum.

### Directions for use: INITIAL APPLICATION

1. Remove old coating and sealer.
  2. Neutralize floor using a neutral cleaner or EnviroStar Green™ All Purpose Neutralizer.
  3. Rinse floor again with clean, cold water and allow to dry.
  4. Apply 2-3 coats of EnviroStar Green Satin Floor Coating with a clean, synthetic mop.
  5. Allow floor to dry thoroughly between coats and prior to burnishing.
- NOTE: To prevent contamination do not pour unused product from bucket into original container.

### Directions for use: ROUTINE MAINTENANCE

1. Sweep floor daily with a dust mop.
2. To clean floor use mop or scrubber with neutral cleaner.
3. As needed, perform a deep scrub and re-coat applying an additional 1-2 coats of EnviroStar Green Satin Floor Coating.
4. Allow floor to dry thoroughly between coats and prior to burnishing.
5. Strip floor when desired results cannot be achieved with routine maintenance.

### Product Data:



CARB compliant



Recognized for Safer Chemistry  
[www.epa.gov/dfe](http://www.epa.gov/dfe)

<b>Description</b>	Polymer emulsion	<b>Coverage</b>	2500 to 3000 ft <sup>2</sup> /gal 61 to 74 m <sup>2</sup> /liter	<b>Buffability</b>	Not required
<b>Appearance</b>	Milky white	<b>Fragrance</b>	Faintly acetic (non-ammoniated)	<b>Removability</b> ASTM D1792-06	Good
<b>Non-volatile solids</b> ASTM D2834-95 (2008)	16%	<b>Slip Resistance</b> UL TM410	Meets requirements	<b>Detergent Resistance</b> ASTM D3207-92 (2008)	Excellent
<b>Specular Gloss (60°)</b> ASTM D1455-87 (2008)	<35	<b>Shelf Life</b> ASTM D1791-93 (2008)	1 year	<b>Drying Time</b>	About 30 minutes
<b>Viscosity (Brookfield)</b> @ 68°F (20°C)	<10 centipoise	<b>Density</b> ASTM D1475-98 (2008)	8.5 lb/gal @ 68°F 1.02 kg/L @ 20°C	<b>Freeze/Thaw</b> ASTM D3209-93 (2008)	Passes 3 cycles

MSDS sheets available for download at [www.pioneer-eclipse.com](http://www.pioneer-eclipse.com)

VOC  
(40 CFR Part 59 Subpart C) 0.89%



Floor Coating and Finishing materials  
as to slip resistance only. 42E6

# Pioneer Eclipse®

©2011 Amano Pioneer Eclipse Corporation® • 1 Eclipse Road • PO Box 909 • Sparta, NC 28675 USA  
1-800-367-3550 • 1-336-372-8080 • Fax: 1-336-372-2895 • [www.pioneer-eclipse.com](http://www.pioneer-eclipse.com)