



We help you shine.™

WONDERGLO®
LOW MAINTENANCE FLOOR COATING

127 WONDERGLO®

LOW MAINTENANCE FLOOR COATING

An excellent, low maintenance, high solids coating with outstanding resistance to scuffs, scratches, black heel marks and detergent scrubbing. Perfect for no or low burnish maintenance programs.

Product Packaging*



PROD CODE: 127FS
 SIZE: 2.50 US gallons (9.5 liters)
 ORDER QTY: 2 per case



PROD CODE: 127FSE
 SIZE: 2.64 US gallons (10 liters)
 ORDER QTY: 2 per case

*Multi-Language Label.



PROD CODE: 127MPE
 SIZE: 1.06 US gallons (4 liters)
 ORDER QTY: 4 per case

*Multi-Language Label.

* Special packaging for specific requirements available upon request.

Product Data:

| | | | | | |
|---|------------------|---|---|---|------------------|
| Description | Polymer emulsion | Coverage | 2500 to 3000 ft ² /gal 61 to 74 m ² /liter | Removability ASTM D1792-06 | Excellent |
| Appearance | Milky white | Fragrance | Slight ammoniacal | Detergent Resistance ASTM D3207-92 (2008) | Excellent |
| Non-volatile solids ASTM D2834-95 (2008) | 22% | Slip Resistance UL TM410 | Meets requirements | Drying Time | About 30 minutes |
| Specular Gloss (60°) ASTM D1455-87 (2008) | >85 | Shelf Life ASTM D1791-93 (2008) | 1 year | Freeze/Thaw ASTM D3209-93 (2008) | Passes 3 cycles |
| Viscosity (Brookfield) @ 68°F (20°C) | <10 centipoise | Density ASTM D1475 (2008) | 8.6 lb/gal @ 68°F 1.03 kg/L @ 20°C | VOC (40 CFR Part 59 Subpart C) | 0.01% |

MSDS sheets available for download at www.pioneer-eclipse.com

Excellent *repairability* from one *tough* floor coating.

Recommended Floor Surfaces:

Vinyl composite tile ("VCT") and hard floor surfaces.

Directions for use: INITIAL APPLICATION

1. Remove old coating and sealer.
2. Neutralize floor using a neutral cleaner or EnviroStar Green™ All Purpose Neutralizer.
3. Rinse floor again with clean, cold water and allow to dry.
OPTIONAL: Apply 2 thin coats of sealer to high-traffic areas and old or porous floors.
4. Apply 4-6 coats of WONDERGLO Low Maintenance Floor Coating with a clean, synthetic mop.
NOTE: Do not exceed an initial application of a combined 6 coats of coating and sealer.
5. Allow floor to dry thoroughly between coats.
NOTE: To prevent contamination do not pour unused product from bucket into original container.

Directions for use: ROUTINE MAINTENANCE

1. Sweep floor daily with a dust mop.
2. To clean floor use mop or scrubber with neutral cleaner.
3. As needed, perform a deep scrub and re-coat applying an additional 1-2 coats of WONDERGLO Low Maintenance Floor Coating.
4. Allow floor to dry thoroughly between coats.
5. Strip floor when desired results cannot be achieved with routine maintenance.

