



We help you shine.™

**STA-BRITE™**  
DRY BRIGHT FLOOR COATING

# 130 STA-BRITE™

shine on.

## DRY BRIGHT FLOOR COATING

An excellent, low maintenance coating with outstanding resistance to scuffs, scratches, black heel marks and detergent scrubbing.

### Product Packaging\*



**PROD CODE: 130FS**  
SIZE: 2.50 US gallons (9.5 liters)  
ORDER QTY: 2 per case



**PROD CODE: 130FSE**  
SIZE: 2.64 US gallons (10 liters)  
ORDER QTY: 2 per case

\*Multi-Language Label.



**PROD CODE: 130MPE**  
SIZE: 1.06 US gallons (4 liters)  
ORDER QTY: 4 per case

\*Multi-Language Label.

\* Special packaging for specific requirements available upon request.

## Our *No buff* formula with high initial *gloss*.

### Recommended Floor Surfaces:

Vinyl composite tile ("VCT") flooring.  
Ideal for floors where ultra high-speed ("UHS") burnishing is not practical.

### Directions for use: INITIAL APPLICATION

1. Remove old coating and sealer.
2. Neutralize floor using a neutral cleaner or EnviroStar Green™ All Purpose Neutralizer.
3. Rinse floor again with clean, cold water and allow to dry.  
OPTIONAL: Apply 2 thin coats of sealer to high-traffic areas and old or porous floors.
4. Apply 5-6 coats of STA-BRITE Floor Coating with a clean, synthetic mop.  
NOTE: Do not exceed an initial application of a combined 6 coats of coating and sealer.
5. Allow floor to dry thoroughly between coats.  
NOTE: Do not pour unused product from bucket into original container.

### Directions for use: ROUTINE MAINTENANCE

1. Sweep floor daily with a dust mop.
2. To clean floor use mop or scrubber with neutral cleaner.
3. As needed, perform a deep scrub and re-coat applying an additional 1-2 coats of STA-BRITE Floor Coating.
4. Allow floor to dry thoroughly between coats.
5. Strip floor when desired results cannot be achieved with routine maintenance.

### Product Data:

<b>Description</b>	Polymer emulsion	<b>Coverage</b>	2500 to 3000 ft <sup>2</sup> /gal 61 to 74 m <sup>2</sup> /liter	<b>Removability</b> ASTM D1792-06	Excellent
<b>Appearance</b>	Milky white	<b>Fragrance</b>	Slight ammoniacal	<b>Detergent Resistance</b> ASTM D3207-92 (2008)	Excellent
<b>Non-volatile solids</b> ASTM D2834-95 (2008)	20%	<b>Slip Resistance</b> UL TM410	Meets requirements	<b>Drying Time</b>	About 30 minutes
<b>Specular Gloss (60°)</b> ASTM D1455-87 (2008)	>85	<b>Shelf Life</b> ASTM D1791-93 (2008)	1 year	<b>Freeze/Thaw</b> ASTM D3209-93 (2008)	Passes 3 cycles
<b>Viscosity (Brookfield)</b> @ 68°F (20°C)	<10 centipoise	<b>Density</b> ASTM D1475-98 (2008)	8.6 lb/gal @ 68°F 1.03 kg/L @ 20°C	<b>VOC</b> (40 CFR Part 59 Subpart C)	0.01%

MSDS sheets available for download at [www.pioneer-eclipse.com](http://www.pioneer-eclipse.com)



Floor Coating and Finishing materials  
as to slip resistance only. 42E6

# Pioneer Eclipse®

©2011 Amano Pioneer Eclipse Corporation® • 1 Eclipse Road • PO Box 909 • Sparta, NC 28675 USA  
1-800-367-3550 • 1-336-372-8080 • Fax: 1-336-372-2895 • [www.pioneer-eclipse.com](http://www.pioneer-eclipse.com)