



We help you shine.™



REBOUND™
CLEANER AND ENHANCER

211 REBOUND™

shine on.

CLEANER AND ENHANCER

An effective one step cleaner and enhancer. May be applied by automatic scrubber or damp-mop. Cleans and enhances coating for a brilliant wet-look shine when burnished with UHS burnishers.

Product Packaging*



PROD CODE: 211FS
SIZE: 2.50 US gallons (9.5 liters)
ORDER QTY: 2 per case



PROD CODE: 211FSE²
SIZE: 2.64 US gallons (10 liters)
ORDER QTY: 2 per case



PROD CODE: 211MPE²
SIZE: 1.06 US gallons (4 liters)
ORDER QTY: 4 per case



PROD CODE: 211DT³
SIZE: 1.06 US gallons (4 liters)
ORDER QTY: 4 per case



PROD CODE: 211DTC³
SIZE: 0.53 US gallons (2 liters)
ORDER QTY: 4 per case

An **effective** cleaner
 and **enhancer** in one.

Recommended Floor Surfaces:

Vinyl composition tile ("VCT") and most types of terrazzo, marble, concrete and quarry tile and treated wood floors.

Directions for use: AUTOMATIC SCRUBBER APPLICATION



DT, DTC: Product to be used only with the AquapHyll™ dilution control system. For recommended **DT 1:64, DTC 1:128 dilution rate**, use AquapHyll™ Portable Plus™ dispenser in bucket setting.

1. Sweep floor with dust mop.
2. Mix REBOUND Cleaner and Enhancer in an automatic scrubber per the following dilution ratio:
 1:32 4 US oz per gallon of water (31 ml per 1 liter of water)
3. Scrub and pick up the solution in one pass.
4. Allow floor to dry thoroughly.
5. Burnish floor.

MOP ON APPLICATION

1. Sweep floor with dust mop.
2. Mix REBOUND Cleaner and Enhancer in mop bucket per the following dilution ratio:
 1:64 2 US oz per gallon of water (16 ml per 1 liter of water)
3. Damp mop the floor using the solution.
4. Allow floor to dry thoroughly.
5. Burnish floor.

1. Special packaging for specific requirements available upon request.
2. Multi-Language Label.
3. For use with AquapHyll dispensing systems.

Product Data:

Description	Water-based cleaner/enhancer	Fragrance	Lemon-lime	Drying Time	Approximately 15 minutes
Appearance	Clear green	Slip Resistance	Meets requirements	Freeze/Thaw	Passes 3 cycles
		UL TM410		ASTM D3209-93 (2008)	
pH	9.0 (as supplied)	Shelf Life	1 year	VOC	0.01% (as supplied)
ASTM E70-07	DTC: 10.5 (as supplied)	ASTM D1791-93 (2008)		(40 CFR Part 59 Subpart C)	<0.01% (1:32 dilution)
Non-volatile solids	11%	Density	8.4 lb/gal @ 68°F	DT: VOC	0.01% (as supplied)
ASTM D2834-95 (2008)	DT: 22%, DTC: 46%	ASTM D1475-98 (2008)	1.01 kg/L @ 20°C	(40 CFR Part 59 Subpart C)	<0.01% (1:64 dilution)
Viscosity (Brookfield)	<10 centipoise	DT, DTC: Density	8.6 lb/gal @ 68°F	DTC: VOC	0.02% (as supplied)
@ 68°F (20°C)		ASTM D1475-98 (2008)	1.03 kg/L @ 20°C	(40 CFR Part 59 Subpart C)	<0% (1:128 dilution)

MSDS sheets available for download at www.pioneer-eclipse.com



Floor Coating and Finishing materials
 as to slip resistance only. 42E6

Pioneer Eclipse®

©2011 Amano Pioneer Eclipse Corporation® • 1 Eclipse Road • PO Box 909 • Sparta, NC 28675 USA
 1-800-367-3550 • 1-336-372-8080 • Fax: 1-336-372-2895 • www.pioneer-eclipse.com