



We help you shine.™

POWERSTAR®
1100 DENSIFYING TREATMENT

419 POWERSTAR® 1100

shine on.

DENSIFYING TREATMENT

Clear, odorless, neutral pH solution that penetrates deep into hard floors. Amorphous silica based product molecularly reacts with floor material to create a harder, more durable surface.

Product Packaging*



PROD CODE: 419GL5
SIZE: 2.50 US gallons (9.5 liters)
ORDER QTY: 2 per case



PROD CODE: 419DR5
SIZE: 55 US gallons (208 liters)
ORDER QTY: 1 Drum

Our **deepest** penetrating
hardener for **hard surface** floors.

Recommended Floor Surfaces:

For concrete, terrazzo, marble and quarry tile floors.

Directions for use:

NOTE: PowerStar 1100 Densifying Treatment is a Ready-to-use ("RTU") product designed to be used as supplied.

1. Apply to a clean floor with low-pressure sprayer. Use a brush or broom to ensure uniform coverage.
2. Keep surface wet with PowerStar 1100 Densifying Treatment for a minimum of 30 minutes.
3. After PowerStar 1100 Densifying Treatment has dried, any un-reacted material can be removed with a broom.

NOTE: Do not walk on floor while the product is drying.

* Special packaging for specific requirements available upon request.

Product Data:

Flash Point ASTM D56-05 (2010)	>200°F (93°C)	pH ASTM E70-07	6.5	Density ASTM D1475-98 (2008)	8.6 lb/gal @ 68°F 1.03 kg/L @ 20°C
Appearance	Clear, colorless liquid	Fragrance	None added	Shelf Life ASTM D1791-93 (2008)	1 year
Viscosity (Brookfield) @ 68°F (20°C)	<10 centipoise				

MSDS sheets available for download at www.pioneer-eclipse.com

Pioneer Eclipse®

©2011 Amano Pioneer Eclipse Corporation® • 1 Eclipse Road • PO Box 909 • Sparta, NC 28675 USA
1-800-367-3550 • 1-336-372-8080 • Fax: 1-336-372-2895 • www.pioneer-eclipse.com