



We help you shine.™



FORMULA X™ UHP
ULTRA HIGH PERFORMANCE STRIPPER

503 FORMULA X™ UHP

ULTRA HIGH PERFORMANCE STRIPPER

Powerful, ultra high performance, non-ammoniated formula cuts through heavy build-up and hard to remove water-based seals in record time.

Product Packaging*



PROD CODE: 503FS
SIZE: 2.50 US gallons (9.5 liters)
ORDER QTY: 2 per case



PROD CODE: 503FSE
SIZE: 2.64 US gallons (10 liters)
ORDER QTY: 2 per case

*Multi-Language Label.



PROD CODE: 503MPE
SIZE: 1.06 US gallons (4 liters)
ORDER QTY: 4 per case

*Multi-Language Label.



PROD CODE: 503A
SIZE: 0.18 US ounces (510 grams)
ORDER QTY: 12 per case

* Special packaging for specific requirements available upon request.

Product Data:

Description	Non-ammoniated, ultra high performance stripper Gel: clinging gel aerosol baseboard stripper	Viscosity (Brookfield) @ 68°F (20°C)	<10 centipoise	Density	8.3 lb/gal @ 68°F ASTM D1475-98 (2008) 1.0 kg/L @ 20°C
Appearance	Clear liquid Gel: Cloudy colorless liquid gel	Fragrance	Citrus	VOC	42% (as supplied) (40 CFR Part 59 Subpart C) 2.42% (1:16)
Flash Point ASTM D56-05 (2010)	150°F (66°C) Gel: N/A	Shelf Life ASTM D1791-93 (2008)	2 years	VOC	4.57% (1:8) (40 CFR Part 59 Subpart C) 8.24% (1:4)

Gel Vapor Pressure 60 psig @ 70°F (21°C)

MSDS sheets available for download at www.pioneer-eclipse.com

Our *fast acting* formula that works *effectively* in cold water.

Recommended Floor Surfaces:

Vinyl composition tile ("VCT"), most types of terrazzo, marble and quarry tile. Not recommended to be used in contact with wood, rubber, painted surfaces or on asphalt or asbestos tile.
NOTE: Test floor for color fastness in an inconspicuous area.

Directions for use:

- Mix Formula X UHP Stripper in a mop bucket or HydroStar™ Stripper Applicator per the following dilution ratios:
For sealer and coating removal (Heavy Removal):
1:4 (32 US oz per gallon or 250 ml per 1 liter cold water).
For finish removal only (Heavy Removal):
1:8 (16 US oz per gallon or 126 ml per 1 liter cold water).
- Apply solution liberally to the floor and allow to soak for 5-10 minutes. Do not let floor dry, keep floor wet using additional solution as required.
- Scrub floor with automatic scrubber or stripping machine.
- Pick up dirty solution with StripVac™ Stripper Recovery Vacuum, automatic scrubber or wet vac.
- Use a clean mop or automatic scrubber to rinse floor twice with a neutral cleaner or use EnviroStar Green™ All Purpose Neutralizer per label instructions.
- Rinse floor again with clean cold water. Allow floor to dry thoroughly before applying sealer or coating.

Gel Stripper Directions for use:

- SHAKE WELL.
- Spray onto surface to be stripped holding can upside down 6 to 10 inches (15-25 cm) from surface. Apply a thin uniform coat of Formula X Baseboard Gel Stripper. Do not overspray.
- Leave on surface for 3 to 5 minutes, then scrub with a wet cleansing sponge or similar tool.
- Rinse thoroughly with clean water.

Always test this product on an inconspicuous area to be cleaned before using. Wipe off any overspray immediately from furniture, walls, and other surfaces.

