

SwingStar®

ELECTRIC BUFFERS

SS1715V, SS2015V, SS2015DV

PRODUCT DATA

FEATURES

- One piece all metal handle housing, tube, and trigger assembly
- Safety lock-out on handle can be easily accessed even with both hands on the handle
- Handle grips are anti-fatigue design and soft to the touch
- Ultra high output motor with lower amp draw for the ultimate in power
- One piece vented, high density polyethylene housing absorbs vibration and controls torque for easy operator control.



SPECIFICATIONS

Cleaning Width:	17 in (43 cm) 20 in (51 cm)	Transmission:	Triple Planetary Drive
Pad/Brush Size:	17 in (43 cm) 20 in (51 cm)	Power Cord:	50 ft (15 m), UL listed 14/3 STW-A
Scrub Pressure:	17 in - 109 lb (50 kg) 20 in - 110 lb (50 kb)	Handle Tube:	All Chrome 1.5 in (4 cm) Floating
Brush Speed:	SS1715V – 175 RPM SS2015V – 175 RPM SS2015DV – 175/320 RPM	Handle Housing:	All Metal, Positive Lock
Operation Control:	Dual lever on-off safety switch	Transport Wheels:	5 in (13 cm) Non-marking Self Lubricating
Motor:	1.5 HP, UL Approved, High Torque	Wiring:	All Completely Enclosed in Housing
		Circuit Breaker:	Convenient, Switch Housing Mounted
		Switch Housing:	Non-conductive Commercial Grade
		Weight:	17 in – 109 lb (50 kg) 20 in – 110 lb (50 kg)