

ECLIPSE® CARPET ALL PURPOSE DEFOAMER

Ready-to-use defoamer to control foaming in carpet extractors

FEATURES

- Effectively reduces foaming in recovery tanks
- Protects vacuum motors from damage due to foam overflow
- Also applicable for autoscrubbers and stripper recovery vacuums



PRODUCT DATA

Description:	Carpet Extraction Defoamer
Appearance:	Milky white liquid
Fragrance:	None added
Viscosity (Brookfield):	300 ± 50 centipoise @ 68°F (20°C)
pH (undiluted):	9.3 ± 0.5 ASTM E70-97
Density:	8.5 lb per gal @ 68°F 1.02 kg per gal @ 20°C
Freeze/Thaw:	Passes 3 cycles ASTM D3209-93 (1998)
Shelf Life:	2 years, ASTM D1791-93 (1998)

PRECAUTIONS:

Keep out of reach of children. Keep container sealed when not in use. Avoid freezing. If frozen, allow to return to room temperature slowly and mix thoroughly before using.

ORDERING INFORMATION

Product #804RTU:	32 US oz (0.95 liter) Twelve bottles per case
------------------	--------------------------------------------------

DIRECTIONS FOR USE:

1. Shake well before using.
2. Add to the carpet extractor recovery tank as needed to control foam.

NOTE: Do not add to floor coatings, finishes or sealers.

ECLIPSE CARPET ALL PURPOSE DEFOAMER

LAST REVISION DATE: 11/26/07
MANUFACTURER: Amano Pioneer Eclipse® Corp.
 Sparta, NC 28675 Phone: 1-336-372-8080
FOR CHEMICAL EMERGENCY: Spill, Leak, Fire,
 Exposure or Accident **CALL CHEMTREC - Day**
or Night 1-800-424-9300 Toll Free in the
 Continental US **483-7616** in DISTRICT OF
 COLUMBIA. For calls originating outside the US:
 Call Collect **1-202-483-7616** Washington, DC.

SECTION I: GENERAL INFORMATION

PRODUCT NAME: Eclipse® Carpet All
 Purpose Defoamer
PRODUCT #: 804
PRODUCT TYPE: Waterbased Carpet Extraction
 Defoamer
PRECAUTIONS: Possible skin and eye irritant.
 Keep container sealed when not in use. Keep out
 of reach of children.


HEALTH: 1

FLAMMABILITY: 0

REACTIVITY: 0

NFPA HAZARD RATINGS

4-EXTREME 3-HIGH 2-MODERATE
 1-SLIGHT 0-INSIGNIFICANT



SECTION II: HAZARDOUS INGREDIENTS

INGREDIENT: Anionic/Nonionic Surfactants
CAS#: N/A
%: 1-3%
OSHA PEL: N/E
ACGIH TLV: N/E
LD₅₀ SPECIES & ROUTE: N/E

N/E = Not Established, N/L = Not Listed
 N/A = Not Applicable

SECTION III: PHYSICAL/CHEMICAL DATA

APPEARANCE: Milky White
PHYSICAL STATE: Liquid
pH: 9.3 ± 0.5
BOILING POINT: 100°C / 212°F
EVAPORATION RATE: Less than water
FREEZING POINT: 0°C / 32°F
VAPOR DENSITY: Greater than air
VOLATILE BY WEIGHT: 97 ± 0.5 %
VAPOR PRESSURE: Less than water
DENSITY: 8.5 lb per gal @ 68°F
 1.02 kg per liter @ 20°C
SOLUBILITY IN WATER: Disperses

SECTION IV: FIRE AND EXPLOSION DATA

FLASH POINT: Non-combustible
EXPLOSIVE LIMITS:
 LOWER: N/A UPPER: N/A
EXTINGUISHING MEDIA: N/A
SPECIAL FIRE FIGHTING PROCEDURES: None
HAZARDOUS COMBUSTIBLE PRODUCTS: None
UNUSUAL FIRE AND EXPLOSION HAZARDS:
 Materials can splatter above 100°C / 212°F.

SECTION V: REACTIVITY DATA

STABILITY: Stable
HAZARDOUS POLYMERIZATION: Will not occur.
INCOMPATIBILITY (MATERIALS TO AVOID):
 Strong acids and bases
HAZARDOUS DECOMPOSITION PRODUCTS: N/A
REACTIVITY CONDITIONS: None

SECTION VI: HEALTH HAZARD DATA

EYES: Slightly irritating to eyes. For eye contact,
 flush with a large amount of water for at least
 15 minutes. See a physician if irritation persists.
SKIN: Slightly irritating to skin upon repeated or
 prolonged contact. For skin contact, wash
 affected areas with soap and water.
INHALATION: Vapor or mist may cause
 irritation of the eyes, nose, throat and lungs. For
 overexposure, move subject to fresh air.
INGESTION: May cause irritation to mouth,
 esophagus and stomach. If ingested, drink
 several glasses of water and do not induce
 vomiting. Seek medical attention.
CHRONIC EFFECTS AND MEDICAL CONDITIONS
AGGRAVATED BY OVEREXPOSURE: Prolonged or
 repeated contact can cause drying, defatting and
 dermatitis to skin.
CARCINOGEN: Non-carcinogenic
REPRODUCTIVE EFFECTS: N/E
TERATOGENICITY: N/E
MUTAGENICITY: N/E
THRESHOLD LIMIT VALUE: See Section II.

SECTION VII: SPILL, LEAK & DISPOSAL PROCEDURES

SMALL SPILLS: Absorb spill with inert material
 (e.g. sand, earth) and dispose of as waste
 material in accordance with local, state and
 federal regulations.
LARGE SPILLS: Keep spectators away. Floors
 may be slippery; use care to avoid falling. Dike
 and contain spill with inert material (e.g. sand,
 earth). Transfer liquid to containers for recovery
 or disposal and solid diking material to separate
 containers for disposal. Keep spills and cleaning
 runoff out of sewers and open bodies of water.
WASTE DISPOSAL: Dispose of as waste
 material in accordance with local, state, and
 federal regulations.

SECTION VIII: SPECIAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT (PPE)
EYES: None required under normal conditions of
 use. Safety glasses recommended.
SKIN: If prolonged or repeated contact is
 possible, chemical-resistant clothing (e.g.,
 rubber gloves) is recommended.
RESPIRATORY: No respiratory protection is
 required if ventilation is adequate.

ENGINEERING CONTROLS: Good general room
 ventilation is expected to be adequate. Local
 exhaust ventilation (e.g., fans) may be necessary
 when general ventilation does not keep airborne
 concentrations below any exposure limits.

SECTION IX: SPECIAL PRECAUTIONS

HANDLING AND STORAGE:
 Storage temperature (MAX. 60°C / 140°F)
 (MIN. 1°C / 34°F)
OTHER PRECAUTIONS: Keep from freezing;
 product may coagulate.

SECTION X: ADDITIONAL INFORMATION

Neither this data sheet nor any statement
 contained herein grants or extends any license,
 expressed or implied, in connection with patents
 issued or pending which may be the property
 of the manufacturer or others. The information
 in this data sheet has been assembled by the
 manufacturer based on its own studies and
 the work of others. The manufacturer makes
 no warranties, expressed or implied, as to the
 accuracy, completeness or adequacy of the
 information contained herein. The manufacturer
 shall not be liable (regardless of fault) or the
 vendee, the vendee's employees or anyone for
 any direct, special or consequential damages
 arising out of or in connection with the accuracy,
 completeness, adequacy or furnishing of such
 information.

This MSDS has been provided to
 you in accordance with the OSHA
 HAZARD COMMUNICATION STANDARD
 (29CFR1910.1200).

***IMPORTANT SAFETY INFORMATION
 DO NOT DISCARD***
 **PLEASE ROUTE TO COMPANY SAFETY
 OFFICER**

