

ENVIROSTAR GREEN® LOW MAINTENANCE FLOOR COATING

An excellent, low maintenance green coating with outstanding resistance to scuffs, scratches, black heel marks and detergent scrubbing

FEATURES

- Ideal for low maintenance (no buff) program
- High long lasting gloss
- Easy to apply and fast drying
- Dries quickly
- Environmentally preferred GREEN formulation



Recognized for Safer Chemistry
www.epa.gov/dfe

RECOMMENDED FLOOR SURFACES

All resilient tile flooring

PRODUCT DATA

Description:	Acrylic co-polymer emulsion
Appearance:	Milky white
Fragrance:	Faintly acetic (non ammoniated)
Coverage:	2500-3000 sq ft per gal 61-74 sq m per liter
Non-Volatile Solids:	20.0 ± 0.5%, ASTM D2834-95 (2001)
Specular Gloss (60°):	>85, ASTM D1455-87 (1997)
Detergent Resistance:	Excellent ASTM D3207-92 (1996) e1
Removability:	Excellent
Viscosity (Brookfield):	<10 centipoise @ 68°F (20°C)
Slip Resistance:	Meets ASTM D2047-99 requirements. Classified by UL as to slip resistance only.
Drying time:	Approximately 30 minutes
Shelf Life:	1 year, ASTM D1791-93 (1998)
Density:	8.6 lb per gal @ 68°F 1.03 kg per liter @ 20°C
Freeze/Thaw:	Passes 3 cycles, ASTM D3209-93 (1998)

PRECAUTIONS

Keep out of the reach of children. Keep container sealed when not in use. Avoid freezing. If frozen, allow to return to room temperature slowly and then mix thoroughly before using.

ORDERING INFORMATION

Product #123FS:	2 x 2.5 gallon per case (2 x 9.5 liter)
Product #123 MP:	4 x 1.06 gallon per case (4 x 4 liter)

DIRECTIONS FOR USE: INITIAL APPLICATION

1. Remove old coating and sealer with the recommended Amano Pioneer Eclipse stripper following label directions. EnviroStar Green Floor Stripper should be used to remove EnviroStar Green floor coatings and sealers, but this stripper is not effective on conventional finished and sealers.
2. Use a clean mop or autoscrubber to rinse the floor twice using EnviroStar Green All Purpose Cleaner. Rinse floor again with clean, cold water and allow to dry.
3. **OPTIONAL:** Apply 2 thin coats of EnviroStar Green Floor Sealer to protect high-traffic areas and old or porous floors.
4. Apply 4-6 coats of EnviroStar Green Low Maintenance Floor Coating with a clean, synthetic mop.
Note: Do not exceed an initial application of a combined 6 coats of coating and sealer.
5. Allow floor to dry thoroughly between coats.
Note: To avoid contamination, do not pour unused product from bucket back into original container.

DIRECTIONS FOR USE: ROUTINE MAINTENANCE

1. Sweep floor daily with either a mop treated with EnviroStar Green Dust Mop Treatment or with an untreated dust mop.
2. Mop or autoscrub as necessary with EnviroStar Green All Purpose Cleaner following label directions.
3. As needed, perform a deep scrub and recoat applying an additional 1-2 coats of EnviroStar Green Low Maintenance Floor Coating.
4. Allow floor to dry thoroughly between coats.
5. When stripping is necessary, remove EnviroStar Green floor coatings with EnviroStar Green Floor Stripper.

ENVIROSTAR GREEN LOW MAINTENANCE FLOOR COATING

LAST REVISION DATE: 11/14/07
MANUFACTURER: Amano Pioneer Eclipse® Corp.
 Sparta, NC 28675 Phone: 1-336-372-8080
FOR CHEMICAL EMERGENCY: Spill, Leak, Fire,
 Exposure or Accident **CALL CHEMTREC - Day**
or Night 1-800-424-9300 Toll Free in the
 Continental US **483-7616** in DISTRICT OF
 COLUMBIA. For calls originating outside the US:
 Call Collect **1-202-483-7616** Washington, DC.

SECTION III: PHYSICAL/CHEMICAL DATA

APPEARANCE: Milky white
PHYSICAL STATE: Liquid
pH: 7.6 ± 0.5
BOILING POINT: 100°C / 212°F
EVAPORATION RATE: Less than water
FREEZING POINT: 0°C / 32°F
VAPOR DENSITY: Greater than air
% VOLATILE BY WEIGHT: 79-81%
VAPOR PRESSURE: Less than water
DENSITY: 8.6 lb per gal @ 68°F
 1.03 kg per liter @ 20°C
SOLUBILITY IN WATER: Miscible

WASTE DISPOSAL: Dispose of as waste material in accordance with local, state, and federal regulations.


SECTION VIII: SPECIAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT (PPE)
EYES: None required under normal conditions of use. Safety glasses recommended.
SKIN: If prolonged or repeated contact is possible, chemical-resistant clothing (e.g., rubber gloves) is recommended.
RESPIRATORY: No respiratory protection is required if ventilation is adequate.

SECTION I: GENERAL INFORMATION

PRODUCT NAME: EnviroStar Green® Low Maintenance Floor Coating
PRODUCT #: 123
PRODUCT TYPE: Acrylic co-polymer emulsion
PRECAUTIONS: Possible skin and eye irritant. Keep container sealed when not in use. Keep out of reach of children.
FLAMMABILITY: 0
REACTIVITY: 0
HEALTH: 1
NFPA HAZARD RATINGS

4-EXTREME 3-HIGH 2-MODERATE
 1-SLIGHT 0-INSIGNIFICANT



SECTION IV: FIRE AND EXPLOSION DATA

FLASH POINT: Non-combustible
EXPLOSIVE LIMITS:
 LOWER: N/A UPPER: N/A
EXTINGUISHING MEDIA: N/A
SPECIAL FIRE FIGHTING PROCEDURES: None
HAZARDOUS COMBUSTIBLE PRODUCTS: None
UNUSUAL FIRE AND EXPLOSION HAZARDS:
 Materials can splatter above 100°C / 212°F.

ENGINEERING CONTROLS: Good general room ventilation is expected to be adequate. Local exhaust ventilation (e.g., fans) may be necessary when general ventilation does not keep airborne concentrations below any exposure limits.

SECTION V: REACTIVITY DATA

STABILITY: Stable
HAZARDOUS POLYMERIZATION: Will not occur.
INCOMPATIBILITY (MATERIALS TO AVOID):
 Strong acids and bases
HAZARDOUS DECOMPOSITION PRODUCTS: N/A
REACTIVITY CONDITIONS: None

SECTION IX: SPECIAL PRECAUTIONS

HANDLING AND STORAGE:
 Storage temperature (MAX. 60°C / 140°F) (MIN. 1°C / 34°F)
OTHER PRECAUTIONS: Keep from freezing; product may coagulate.

SECTION II: INGREDIENTS

INGREDIENT: Water
CAS#: 7732-18-5
%: 45-50
OSHA PEL: N/E
ACGIH TLV: N/E
LD₅₀ SPECIES & ROUTE: N/E

INGREDIENT: Aqueous Acrylic Emulsion
CAS#: N/E
%: 40-45
OSHA PEL: N/E
ACGIH TLV: N/E
LD₅₀ SPECIES & ROUTE: N/E

INGREDIENT: Dipropylene glycol methyl ether
CAS#: 34590-94-8
%: 2-5
OSHA PEL: N/E
ACGIH TLV: 100 ppm, 8 HRS TWA
LD₅₀ SPECIES & ROUTE: 5.35 g/kg rat, oral

INGREDIENT: Tributoxy ethyl phosphate
CAS#: 78-51-3
%: 2-5
OSHA PEL: N/E
ACGIH TLV: N/E
LD₅₀ SPECIES & ROUTE: N/E

INGREDIENT: Polyethylene emulsion
CAS#: N/E
%: 1-3
OSHA PEL: N/E
ACGIH TLV: N/E
LD₅₀ SPECIES & ROUTE: N/E

N/E = Not Established N/L = Not Listed
 N/A = Not Applicable

SECTION VI: HEALTH HAZARD DATA

EYES: Slightly irritating to eyes. For eye contact, flush with a large amount of water for at least 15 minutes. See a physician if irritation persists.
SKIN: Slightly irritating to skin upon repeated or prolonged contact. For skin contact, wash affected areas with soap and water.
INHALATION: Vapor or mist may cause irritation of the eyes, nose, throat and lungs. For overexposure, move subject to fresh air.
INGESTION: May cause irritation to mouth, esophagus and stomach. If ingested, drink several glasses of water and do not induce vomiting. Seek medical attention.
CHRONIC EFFECTS AND MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE: Prolonged or repeated contact can cause drying, defatting and dermatitis to skin.
CARCINOGEN: Non-carcinogenic
REPRODUCTIVE EFFECTS: N/E
TERATOGENICITY: N/E
MUTAGENICITY: N/E
THRESHOLD LIMIT VALUE: See Section II.

SECTION X: ADDITIONAL INFORMATION

Neither this data sheet nor any statement contained herein grants or extends any license, expressed or implied, in connection with patents issued or pending which may be the property of the manufacturer or others. The information in this data sheet has been assembled by the manufacturer based on its own studies and the work of others. The manufacturer makes no warranties, expressed or implied, as to the accuracy, completeness or adequacy of the information contained herein. The manufacturer shall not be liable (regardless of fault) or the vendee, the vendee's employees or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnishing of such information.

This MSDS has been provided to you in accordance with the OSHA HAZARD COMMUNICATION STANDARD (29CFR1910.1200).

***IMPORTANT SAFETY INFORMATION
 DO NOT DISCARD***
 PLEASE ROUTE TO COMPANY SAFETY OFFICER

SECTION VII: SPILL, LEAK & DISPOSAL PROCEDURES

SMALL SPILLS: Absorb spill with inert material (e.g. sand, earth) and dispose of as waste material in accordance with local, state and federal regulations.
LARGE SPILLS: Keep spectators away. Floors may be slippery; use care to avoid falling. Dike and contain spill with inert material (e.g. sand, earth). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for disposal. Keep spills and cleaning runoff out of sewers and open bodies of water.

