

STAR-TECH™ LOW MAINTENANCE FLOOR COATING

A high quality, low maintenance coating with outstanding resistance to scuffs, scratches, black heel marks and detergent scrubbing

FEATURES

- Ideal for low maintenance program
- Formulated to achieve significant labor savings
- High initial gloss
- Easy to apply
- Dries quickly
- Self-sealing



RECOMMENDED FLOOR SURFACES

All resilient tile flooring

PRODUCT DATA

Description:	Acrylic co-polymer emulsion
Appearance:	Milky white
Fragrance:	Slight ammoniacal
Coverage:	2500-3000 sq ft per gal 61-74 sq m per liter
Non-Volatile Solids:	16.0 ± 0.5%, ASTM D2834-95 (2001)
Specular Gloss (60°):	>85, ASTM D1455-87 (1997)
Detergent Resistance:	Excellent ASTM D3207-92 (1996) e1
Removability:	Excellent
Viscosity (Brookfield):	<10 centipoise @ 68°F (20°C)
Slip Resistance:	Meets ASTM D2047-99 requirements. Classified by UL as to slip resistance only.
Drying time:	Approximately 30 minutes
Shelf Life:	1 year, ASTM D1791-93 (1998)
Density:	8.6 lb per gal @ 68°F 1.03 kg per liter @ 20°C
Freeze/Thaw:	Passes 3 cycles, ASTM D3209-93 (1998)

PRECAUTIONS

Keep out of the reach of children. Keep container sealed when not in use. Avoid freezing. If frozen, allow to return to room temperature slowly and then mix thoroughly before using.

ORDERING INFORMATION

Product #126FS: 2 x 2.50 gallon per case (2 x 9.5 liter)

DIRECTIONS FOR USE: INITIAL APPLICATION

1. Remove old coating and sealer with Amano Pioneer Eclipse floor stripper following label directions. For best results use stripping machine with Amano Pioneer Eclipse pads or brushes.
2. Use a clean mop or autoscrubber to rinse the floor twice using an Amano Pioneer Eclipse neutral cleaner following label directions. Rinse floor again with clean cold water and allow to dry.
3. **OPTIONAL:** Apply 2 thin coats of recommended Amano Pioneer Eclipse Sealer to protect high traffic areas and old or porous floors. Allow floor to dry between coats.
4. Apply 4-6 thin coats of Star-Tech Low Maintenance Floor Coating with a clean synthetic mop. Allow floor to dry thoroughly between coats.

Note: Do not exceed more than 6 initial coats of sealer and coating combined.
5. Allow floor to dry thoroughly between coats and prior to burnishing.
6. **OPTIONAL:** Burnish as desired with recommend Amano Pioneer Eclipse machine and pad.

Note: To avoid possible contamination do not pour unused product from mop bucket back into original container.

DIRECTIONS FOR USE: ROUTINE MAINTENANCE

1. Sweep floor daily using a mop treated with EnviroStar Green® Dust Mop Treatment or with an untreated dust mop.
2. Mop or autoscrub as necessary with an Amano Pioneer Eclipse neutral cleaner following label directions.
3. Scrub and recoat as needed with 1-2 thin coats of Star-Tech Low Maintenance Floor Coating.
4. Allow floor to dry thoroughly between coats.
5. Optional: Burnish as desired with recommend Amano Pioneer Eclipse machine and pad.
6. When stripping is necessary, remove coating using recommended Amano Pioneer Eclipse floor stripper following label directions.

STAR-TECH FLOOR COATING

LAST REVISION DATE: 11/26/07
MANUFACTURER: Amano Pioneer Eclipse® Corp.
 Sparta, NC 28675 Phone: 1-336-372-8080
FOR CHEMICAL EMERGENCY: Spill, Leak, Fire,
 Exposure or Accident **CALL CHEMTREC - Day**
or Night 1-800-424-9300 Toll Free in the
 Continental US **483-7616** in DISTRICT OF
 COLUMBIA. For calls originating outside the US:
 Call Collect **1-202-483-7616** Washington, DC.

SECTION IV: FIRE AND EXPLOSION DATA


FLASH POINT: Non-combustible
EXPLOSIVE LIMITS:
 LOWER: N/A UPPER: N/A
EXTINGUISHING MEDIA: N/A
SPECIAL FIRE FIGHTING PROCEDURES: None
HAZARDOUS COMBUSTIBLE PRODUCTS: None
UNUSUAL FIRE AND EXPLOSION HAZARDS:
 Materials can splatter above 100°C / 212°F.

SECTION VIII: SPECIAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT (PPE)
EYES: None required under normal conditions of use. Safety glasses recommended.
SKIN: If prolonged or repeated contact is possible, chemical-resistant clothing (e.g., rubber gloves) is recommended.
RESPIRATORY: No respiratory protection is required if ventilation is adequate.
ENGINEERING CONTROLS: Good general room ventilation is expected to be adequate. Local exhaust ventilation (e.g., fans) may be necessary when general ventilation does not keep airborne concentrations below any exposure limits.

SECTION I: GENERAL INFORMATION

PRODUCT NAME: Star-Tech™ Low Maintenance Floor Coating
PRODUCT #: 126
PRODUCT TYPE: Acrylic co-polymer emulsion
PRECAUTIONS: Possible skin and eye irritant. Keep container sealed when not in use. Keep out of reach of children.
HEALTH: 1
FLAMMABILITY: 0
REACTIVITY: 0
NFPA HAZARD RATINGS



4-EXTREME 3-HIGH 2-MODERATE
 1-SLIGHT 0-INSIGNIFICANT

SECTION II: HAZARDOUS INGREDIENTS

INGREDIENT: *Diethylene glycol monoethyl ether
CAS#: 111-90-0
%: 3-7
OSHA PEL: N/E
ACGIH TLV: N/E
LD₅₀ SPECIES & ROUTE: 5.5 g/kg male rat, oral
 9.0 g/kg rabbit, skin

* This chemical is subject to the reporting requirements of Section 313 of SARA Title III.

N/E = Not Established, N/L = Not Listed,
 N/A = Not Applicable

SECTION V: REACTIVITY DATA

STABILITY: Stable
HAZARDOUS POLYMERIZATION: Will not occur
INCOMPATIBILITY (MATERIALS TO AVOID):
 Strong acids and bases
HAZARDOUS DECOMPOSITION PRODUCTS: N/A
REACTIVITY CONDITIONS: None

SECTION IX: SPECIAL PRECAUTIONS

HANDLING AND STORAGE:
 Storage temperature (MAX. 60°C / 140°F)
 (MIN. 1°C / 34°F)
OTHER PRECAUTIONS: Keep from freezing; product may coagulate.

SECTION VI: HEALTH HAZARD DATA

EYES: Slightly irritating to eyes. For eye contact, flush with a large amount of water for at least 15 minutes. See a physician if irritation persists.
SKIN: Slightly irritating to skin upon repeated or prolonged contact. For skin contact, wash affected areas with soap and water.
INHALATION: Vapor or mist may cause irritation of the eyes, nose, throat and lungs. For overexposure, move subject to fresh air.
INGESTION: May cause irritation to mouth, esophagus and stomach. If ingested, drink several glasses of water and do not induce vomiting. Seek medical attention.
CHRONIC EFFECTS AND MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE: Prolonged or repeated contact can cause drying, defatting and dermatitis to skin.
CARCINOGEN: Non-carcinogenic
REPRODUCTIVE EFFECTS: N/E
TERATOGENICITY: N/E
MUTAGENICITY: N/E
THRESHOLD LIMIT VALUE: See Section II.

SECTION X: ADDITIONAL INFORMATION

Neither this data sheet nor any statement contained herein grants or extends any license, expressed or implied, in connection with patents issued or pending which may be the property of the manufacturer or others. The information in this data sheet has been assembled by the manufacturer based on its own studies and the work of others. The manufacturer makes no warranties, expressed or implied, as to the accuracy, completeness or adequacy of the information contained herein. The manufacturer shall not be liable (regardless of fault) or the vendee, the vendee's employees or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnishing of such information.

This MSDS has been provided to you in accordance with the OSHA HAZARD COMMUNICATION STANDARD (29CFR1910.1200).

SECTION III: PHYSICAL/CHEMICAL DATA

APPEARANCE: Milky white
PHYSICAL STATE: Liquid
pH: 8.7 ± 0.5
BOILING POINT: 100°C / 212°F
EVAPORATION RATE: Less than water
FREEZING POINT: 0°C / 32°F
VAPOR DENSITY: Greater than air
VOLATILE BY WEIGHT: 80.0 ± 0.5%
VAPOR PRESSURE: Less than water
DENSITY: 8.6 lb per gal @ 68°F
 1.03 kg per liter @ 20°C
SOLUBILITY IN WATER: Miscible

SECTION VII: SPILL, LEAK & DISPOSAL PROCEDURES

SMALL SPILLS: Absorb spill with inert material (e.g. sand, earth) and dispose of as waste material in accordance with local, state and federal regulations.
LARGE SPILLS: Keep spectators away. Floors may be slippery; use care to avoid falling. Dike and contain spill with inert material (e.g. sand, earth). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for disposal. Keep spills and cleaning runoff out of sewers and open bodies of water.
WASTE DISPOSAL: Dispose of as waste material in accordance with local, state, and federal regulations.

***IMPORTANT SAFETY INFORMATION
 DO NOT DISCARD***
 PLEASE ROUTE TO COMPANY SAFETY OFFICER

