

**LASERSHOT™
SPRAY & WIPE DEGREASER**

Powerful, heavy duty all purpose degreaser

FEATURES

- *Powerful, super fast degreaser*
- *Pleasant fragrance*
- *Cleans grease, oils, lipsticks, crayons, etc.*
- *Concentrated for economical use*

**RECOMMENDED SURFACES**

Before LaserShot is used, test surface to be cleaned in an inconspicuous area for color fastness and surface compatibility.

PRODUCT DATA

Description:	Powerful, heavy duty all purpose degreaser concentrate
Appearance:	Clear red liquid
Fragrance:	Spearmint
Viscosity (Brookfield):	<10 centipoise @ 68°F (20°C)
pH (undiluted):	13.0± 0.5 ASTM E70-97
Density:	8.3 lb per gal @ 68°F 0.99 kg per liter @ 20°C
Flash Point:	150°F (66°C), ASTM D56
Freeze/Thaw:	Passes 3 cycles ASTM D3209-93 (1998)
Shelf Life:	2 years, ASTM D1791-93 (1998)

PRECAUTIONS

Keep out of reach of children. Keep container sealed when not in use. Keep from freezing. Combustible. Gloves and safety glasses are recommended.

ORDERING INFORMATION

Product #323D: 4 x 1.06 gallon per case (4 x 4 liters)

DIRECTIONS FOR USE: GENERAL CLEANING:

1. Mix LaserShot per the following dilution ratio:
1:6 21 US oz per gallon water (140 ml per 1 liter water)
2. Spray surface and wipe with clean cloth or paper towel.
No rinse needed.

LASERSHOT SPRAY & WIPE DEGREASER

LAST REVISION DATE: 12/5/07
MANUFACTURER: Amano Pioneer Eclipse® Corp.
 Sparta, NC 28675 Phone: 1-336-372-8080
FOR CHEMICAL EMERGENCY: Spill, Leak, Fire, Exposure or Accident **CALL CHEMTREC - Day or Night 1-800-424-9300** Toll Free in the Continental US **483-7616** in DISTRICT OF COLUMBIA. For calls originating outside the US: Call Collect **1-202-483-7616** Washington, DC.

SECTION I: GENERAL INFORMATION

PRODUCT NAME: LaserShot™ Spray & Wipe Degreaser
PRODUCT #: 323D
PRECAUTIONS: Corrosive. Do not get in eyes, on skin or clothing. Keep container sealed when not in use. Keep out of reach of children.
FLAMMABILITY: 2
REACTIVITY: 0
HEALTH: 2
NFPA HAZARD RATINGS
 4-EXTREME 3-HIGH 2-MODERATE
 1-SLIGHT 0-INSIGNIFICANT



SECTION II: HAZARDOUS INGREDIENTS

INGREDIENT: Ethanol, 2-Amino
CAS#: 141-43-5
%: 10-15
OSHA PEL: 3 ppm (TWA)
ACGIH TLV: 3 ppm (TWA) 6 ppm (STEL)
LD₅₀ SPECIES & ROUTE: 1.2 g/kg rat, oral

INGREDIENT: *Ethanol, 2-Butoxy
CAS#: 111-76-2
%: 35-40
OSHA PEL: 50 ppm (skin) (TWA)
ACGIH TLV: 20 ppm (TWA)
LD₅₀ SPECIES & ROUTE: 0.5g/kg rat, oral

* This chemical is subject to the reporting requirements of Section 313 of SARA Title III.

N/E = Not Established, N/L = Not Listed
 N/A = Not Applicable

SECTION III: PHYSICAL/CHEMICAL DATA

APPEARANCE: Clear red liquid
PHYSICAL STATE: Liquid
pH: 13.0 ± 0.5
BOILING POINT: 100°C / 212°F
EVAPORATION RATE: Less than water
FREEZING POINT: 0°C / 32°F
VAPOR DENSITY: Greater than air
VOLATILE BY WEIGHT: 97-99%
VAPOR PRESSURE: N/E
DENSITY: 8.3 lb per gal @ 68°F
 0.99 kg per liter @ 20°C
SOLUBILITY IN WATER: Miscible

SECTION IV: FIRE AND EXPLOSION DATA

FLASH POINT: 150°F (66°C) ASTM D56
EXPLOSIVE LIMITS:
 LOWER: N/E UPPER: N/E
EXTINGUISHING MEDIA: Water spray, CO₂, dry chemical, alcohol-type or universal type foams.
SPECIAL FIRE FIGHTING PROCEDURES: Do not spray a solid stream of water or foam directly into hot liquid. This may cause frothing. Firefighters should wear NIOSH approved breathing apparatus.
HAZARDOUS COMBUSTIBLE PRODUCTS: N/A
UNUSUAL FIRE AND EXPLOSION HAZARDS: Materials can splatter above 100°C / 212°F.

SECTION V: REACTIVITY DATA

STABILITY: Stable
HAZARDOUS POLYMERIZATION: Will not occur.
INCOMPATIBILITY (MATERIALS TO AVOID): Strong acids and bleach.
HAZARDOUS DECOMPOSITION PRODUCTS: None Known
REACTIVITY CONDITIONS: None

SECTION VI: HEALTH HAZARD DATA

EYES: May cause severe burns or possible corneal damage. For eye contact, flush with a large amount of water for at least 15 minutes. See a physician immediately.
SKIN: Irritation, reddening or possible damage upon repeated or prolonged contact. For skin contact, wash affected areas with soap and water. Seek medical attention if irritation persists.
INHALATION: Vapor or mist can cause headache, nausea and irritation of the eyes, nose, throat and lungs. For overexposure, move subject to fresh air. Seek medical attention if symptoms persist.
INGESTION: May cause nausea, abdominal discomfort, vomiting, diarrhea. If ingested, drink two glasses of water or milk and do not induce vomiting. Remove by endotracheal intervention. Seek medical attention immediately.
CHRONIC EFFECTS AND MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE: Main hazard is due to product's severe irritant properties. Treatment should be directed at the control of symptoms and the clinical condition of the patient.
CARCINOGEN: Non-carcinogenic
REPRODUCTIVE EFFECTS: N/E
TERATOGENICITY: N/E
MUTAGENICITY: N/E
THRESHOLD LIMIT VALUE: See Section II.

SECTION VII: SPILL, LEAK & DISPOSAL PROCEDURES

SMALL SPILLS: Absorb spill with inert material (e.g. sand, earth) and dispose of as waste material in accordance with local, state and federal regulations. Neutralize residue with vinegar, mild acid or large amount of water.

LARGE SPILLS: Keep spectators away. Floors may be slippery; use care to avoid falling. Dike and contain spill with inert material (e.g. sand, earth). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for disposal. Keep spills and cleaning runoff out of sewers and open bodies of water.
WASTE DISPOSAL: Landfill or incinerate the contaminated solids and diking material according to local, state and federal regulations concerning disposal of hazardous materials. Non-salvageable liquid should be drummed and turned over to a licensed hazardous waste disposal facility.

SECTION VIII: SPECIAL PROTECTION

EYE PROTECTION: Chemical splash goggles (ANSI Z87.1-1989 or approved equivalent)
RESPIRATORY PROTECTION: None required when permissible airborne concentrations are not exceeded. In emergency, use approved positive pressure self-contained breathing device.
VENTILATION: Mechanical local exhaust ventilation at point of contamination release.
OTHER PROTECTIVE EQUIPMENT: As required by employer code. Rubber boots and chemical resistant gloves recommended.

SECTION IX: SPECIAL PRECAUTIONS

HANDLING AND STORAGE: Storage temperature (MAX. 60°C / 140°F) (MIN. 1°C / 34°F).
OTHER PRECAUTIONS: Keep from freezing

SECTION X: ADDITIONAL INFORMATION

Neither this data sheet nor any statement contained herein grants or extends any license, expressed or implied, in connection with patents issued or pending which may be the property of the manufacturer or others. The information in this data sheet has been assembled by the manufacturer based on its own studies and the work of others. The manufacturer makes no warranties, expressed or implied, as to the accuracy, completeness or adequacy of the information contained herein. The manufacturer shall not be liable (regardless of fault) or the vendee, the vendee's employees or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnishing of such information.

This MSDS has been provided to you in accordance with the OSHA HAZARD COMMUNICATION STANDARD (29CFR1910.1200).

***IMPORTANT SAFETY INFORMATION
 DO NOT DISCARD***
 PLEASE ROUTE TO COMPANY SAFETY OFFICER

